WOLF'S RANGE OF TRIPODS ARE LIGHTWEIGHT, EASILY TRANSPORTABLE AND WILL EXTEND A LAMP TO A MAXIMUM HEIGHT OF 3.2 METRES.

Once assembled a tripod gives a stable platform allowing the LinkEx™ LED Temporary Luminaires, Portable Fluorescent Leadlamps, LED Floodlites and XT Flood Bank Stands to be used at a variety of heights and positions. The tripod allows the positioning of a lamp to deliver vertical or horizontal forward facing light or in the horizontal position the light can be directed upwards illuminating the work area from the underside.

Three models available:

- Lightweight – Steel (Black Painted) – max. height 1.85m
- Medium Duty - Steel (Plated) – max. height 2.4m
- Heavy Duty – Steel (Plated) – max. height 3.2m

A mounting bracket is required for the LinkEx™ LED Temporary Luminaire and Portable Fluorescent Leadlamp to attach to the tripod and position the lamp either horizontally or vertically. An optional mounting bracket is available for the LinkEx™ LED Floodlites and XT Flood Bank Stands (for the Medium and Heavy Duty Tripods only) to attach to the lamp/tripod and facilitate an easy removal of the lamp for frequent positioning at ground level.

IMPA Code
33 19 42 / 33 19 32 - LL-680
33 19 33 - LL-690, 33 19 34 - LL-695

| Product | Description |
|---|---|
| LL-680 | Lightweight Tripod - 1.85m<br>REQUEST A QUOTE |
| LL-699 | Medium Duty Tripod - 2.4m<br>REQUEST A QUOTE |
| LL-668 | Heavy Duty Tripod - 3.2m<br>REQUEST A QUOTE |
| LX-670 | Tripod Mounting Bracket (LinkEx™ LED Temporary Luminaire LX-400)<br>REQUEST A QUOTE |

| Product | Description |
|---|---|
| LL-669 | Tripod Mounting Bracket (LinkEx™ LED Floodlite and XT Flood Bank Stands) - For Medium and Heavy Duty Tripods only. Optional for frequent removal from tripod and repositioning of lamp at ground level.<br>REQUEST A QUOTE |

| Product Reference | | LL-680 | | LL-699 | | LL-668 | |
|---|---|---|---|---|---|---|---|
| Product Description | | Lightweight Tripod Stand | | Medium Duty Tripod Stand | | Heavy Duty Tripod Stand | |
| Material | | Steel - Black Painted | | Steel - Plated | | Steel - Plated | |
| Height (Extends To) | | 1.85m | | 2.4m | | 3.2m | |
| Suitable For | | LL-500, LX-400, WF-300 and XT-4XX/6XX Ranges | | | | | |
| Mounting Bracket | LL-500 | LL-690 (2x36W Lamp) | LL-695 (4x36W Lamp) | LL-690 (2x36W Lamp) | LL-695 (4x36W Lamp) | LL-690 (2x36W Lamp) | LL-695 (4x36W Lamp) |
| | LX-400 | LX-670 | | | | | |
| | WF-300 | Not Required | | LL-669 (optional)<br>For frequent removal from tripod and repositioning of lamp at ground level. | | | |
| | XT-4XX / 6XX | Not Required | | | | | |

- All information has been gathered under laboratory conditions, the user must regard the values given as approximate.

- Changes may be made to the above specification without notification, details are available on request.