WOLF'S EXTENSIVE RANGE OF POSITIONING, MOUNTING AND PROTECTION ACCESSORIES, ENCOMPASSING FIXING KITS, FILMS AND CABLE MANAGEMENT, FOR THE LINKEX™ LED TEMPORARY LUMINAIRE (LX-400) GIVE WORKERS MORE SECURE TEMPORARY INSTALLATION SOLUTIONS FOR TEMPORARY LIGHTING IN HAZARDOUS AREA WORKING ENVIRONMENTS.

Wolf's LinkEx™ LED Temporary Luminaire plastic brackets, with snap shut mechanism and screw to lock securely closed around a luminaire, form a key component of all Wolf's fixing kits giving flexible and sturdy mounting and positioning options for temporary applications. Securely mount or hang a luminaire almost anywhere and in any orientation - putting the luminaire exactly where it is needed.

FIXING KITS

- Bracket Kit - With brackets and screws fix directly to flat walls.
- Magnet Bracket Kit - With magnet pads grip to flat ferrous metal surfaces.
- Scaffold Bracket Kit - With stainless steel pipe clamps with rubber linings fit to standard poles 47 to 51 mm diameter.
- Unistrut Bracket Kit - With unistrut nuts attach to standard channel systems.
- Eye Bolt / Dual Eye Bracket Kit - With eye bolts suspend with carabiners and S hooks from existing infrastructure.
- Tripod Bracket Kit - With fixing bar attach horizontally or vertically to tripod stand.
- Hanging Straps - With straps hang from existing infrastructure.

Note: Each kit contains the brackets to mount one LinkEx™ LED Temporary Luminaire or two lights where Dual specified.

TRIPODS

For standalone luminaire positioning, Wolf's tripods give a stable platform allowing the luminaire to be attached with the Tripod Bracket Kit and used at a variety of heights and positions to deliver vertical or horizontal forward facing light, in the horizontal position the light can be directed upwards, illuminating the work area from the underside. The range of Tripod Stands available are lightweight, easily transportable, made from steel and will extend a lamp to a height of up to 3.2 metres and are ideal for both '180°' (unidirectional illumination) and '360°' (omni-directional 'all round' illumination) luminaires to maximise light area coverage for workers.

FILMS / CABLE MANAGEMENT

Not only is the positioning and mounting of luminaires key to worker efficiency but also the protection of the outer tube from damage to ensure its longevity, in optimal condition, for repeat usage. Wolf luminaires are used regularly in blasting, jetting, coating and painting applications and are protected from residue build-up

by the use of a Protective Film, easily replaced between uses to ensure the product is delivering maximum light output without obstructions. Each film is supplied with an easy peel foam back adhesive for ease of application.
Similarly if the luminaire is deemed too bright, when being used in a confined space at head height by a worker, an Internal Diffuser Film can be installed to minimise glare. Finally, to keep the working area free from potential trip hazards, cable can be managed using a Magnet Cable Tidy to elevate it from the ground along a ferrous metal surface.
If you require something different to suit a particular hazardous area need, whether a variation to our existing range or a totally new accessory for a unique application and environment, please contact us to discuss the development of a practical and safe accessory solution.

Product	Description
LX-690	Bracket Kit (To mount one LX-400) REQUEST A QUOTE
LX-680	Magnet Bracket Kit (To mount one LX-400) REQUEST A QUOTE
LX-671	Eye Bolt Bracket Kit (To mount one LX-400) REQUEST A QUOTE
LX-672	Dual Eye Bracket Kit (To mount two LX-400s side-by-side) REQUEST A QUOTE
LX-678	Scaffold Bracket Kit (To mount one LX-400) REQUEST A QUOTE
LX-670	Tripod Bracket Kit (To mount one LX-400) REQUEST A QUOTE
LX-679	Unistrut Bracket Kit (To mount one LX-400) REQUEST A QUOTE

Product	Description
LX-654	Hanging Straps (2 straps per pack) REQUEST A QUOTE
LX-545/3	Protective Film (3 per pack) REQUEST A QUOTE
LX-374	Internal Diffuser Film (1 per pack) REQUEST A QUOTE
LX-692	Magnet Cable Tidy (1 per pack) REQUEST A QUOTE
LX-674	S Hook (2 per pack) REQUEST A QUOTE
LX-675	Carabiner (2 per pack) REQUEST A QUOTE

Product Reference	Product Description	Notes
LX-690	Bracket Kit	To mount one LX-400
LX-680	Magnet Bracket Kit	To mount one LX-400
LX-671	Eye Bolt Bracket Kit	To mount one LX-400
LX-672	Dual Eye Bracket Kit	To mount two LX-400s side-by-side
LX-678	Scaffold Bracket Kit	To mount one LX-400

LX-670	Tripod Bracket Kit	To mount one LX-400 on a Tripod Stand
LX-679	Unistrut Bracket Kit	To mount one LX-400
LX-654	Hanging Straps	2 straps per pack
LX-674	S Hook	2 per pack - Length 150mm / Throat 55mm
LX-675	Carabiner	2 per pack - Length 120mm / Gate 17mm
LX-545/3	Protective Film	3 per pack
LX-374	Internal Diffuser Film	1 per pack
LX-692	Magnet Cable Tidy	1 per pack

- All information has been gathered under laboratory conditions, the user must regard the values given as approximate.
- Changes may be made to the above specification without notification, details are
- available on request.

WOLF'S RANGE OF TRIPODS ARE LIGHTWEIGHT, EASILY TRANSPORTABLE AND WILL EXTEND A LAMP TO A MAXIMUM HEIGHT OF 3.2 METRES.

Once assembled a tripod gives a stable platform allowing the LinkEx™ LED Temporary Luminaires, Portable Fluorescent Leadlamps, LED Floodlites and XT Flood Bank Stands to be used at a variety of heights and positions. The tripod allows the positioning of a lamp to deliver vertical or horizontal forward facing light or in the horizontal position the light can be directed upwards illuminating the work area from the underside.

Three models available:

- Lightweight – Steel (Black Painted) – max. height 1.85m
- Medium Duty - Steel (Plated) – max. height 2.4m
- Heavy Duty – Steel (Plated) – max. height 3.2m

A mounting bracket is required for the LinkEx™ LED Temporary Luminaire and Portable Fluorescent Leadlamp to attach to the tripod and position the lamp either horizontally or vertically. An optional mounting bracket is available for the LinkEx™ LED Floodlites and XT Flood Bank Stands (for the Medium and Heavy

Duty Tripods only) to attach to the lamp/tripod and facilitate an easy removal of the lamp for frequent positioning at ground level.

IMPA Code
33 19 42 / 33 19 32 - LL-680
33 19 33 - LL-690, 33 19 34 - LL-695

Product	Description
LL-680	Lightweight Tripod - 1.85m REQUEST A QUOTE
LL-699	Medium Duty Tripod - 2.4m REQUEST A QUOTE
LL-668	Heavy Duty Tripod - 3.2m REQUEST A QUOTE
LX-670	Tripod Mounting Bracket (LinkEx™ LED Temporary Luminaire LX-400) REQUEST A QUOTE
LL-669	Tripod Mounting Bracket (LinkEx™ LED Floodlite and XT Flood Bank Stands) - For Medium and Heavy Duty Tripods only. Optional for frequent removal from tripod and repositioning of lamp at ground level. REQUEST A QUOTE

Product Reference	LL-680	LL-699	LL-668
Product Description	Lightweight Tripod Stand	Medium Duty Tripod Stand	Heavy Duty Tripod Stand
Material	Steel - Black Painted	Steel - Plated	Steel - Plated
Height (Extends	1.85m	2.4m	3.2m

To)							
Suitable For		LL-500, LX-400, WF-300 and XT-4XX/6XX Ranges					
Mounting Bracket	LL-500	LL-690 (2x36W Lamp)	LL-695 (4x36W Lamp)	LL-690 (2x36W Lamp)	LL-695 (4x36W Lamp)	LL-690 (2x36W Lamp)	LL-695 (4x36W Lamp)
	LX-400	LX-670					
	WF-300	Not Required	LL-669 (optional) For frequent removal from tripod and repositioning of lamp at ground level.				
	XT-4XX / 6XX	Not Required					

- All information has been gathered under laboratory conditions, the user must regard the values given as approximate.
- Changes may be made to the above specification without notification, details are available on request.