FLOOR WAX

Rub-on styrene / acrylic wax for sustainable maintenance of hard floors.

(Code 859) - 5L

pH

1 2 3 4 5 6 7 **8** 9 10 11 12 13 14

Properties

Gives the treated floor a lovely, deep shine. Extremely suitable for most types of flat, water-resistant hard floors such as vinyl, rubber, linoleum, marble and laminate. Can be rubbed on with the aid of a rotary machine. Preferably only use fully stripped, rinsed, dry floors.

Dosage and Use

Remove the old wax layers first with Americol Floor Wax Stripper. Rinse the floor thoroughly and allow to dry. Pour the undiluted product onto the floor and spread immediately with a suitable polish applicator in strips measuring 1-1.5 metres, allowing them to overlap if the floor is still wet. Preferably, apply at least 2 coats. Use Approx. 1 litre for every 10-20 m2. Use on water-resistant floors only.

Americol BV ⩔ Sluispolderweg 33 ⩔ 1505 HJ Zaandam ⩔ The Netherlands ⩔ T: +31 (0)75 - 631 32 44 ⩔ info@americol.nl ⩔ www.americol.nl
ING Bank: 66.01.71.104 ⩔ BIC: INGBNL2A ⩔ IBAN: NL46INGB0660171104 ⩔ BTW/VAT: NL802941862B01 ⩔ KvK Zaandam: 35025350