RESPIRATORY PROTECTION

# HALF MASKS
# POLIMASK® 230/EF+VS A1 P1

One size rubber respirator with one combined cartridge type 230 EF+VS A1 P1, organic gas and vapours, dust and fumes. Suitable for spray painting and agriculture. Complying with EN 140 and EN 14387.

## MAIN FEATURES

- **Component materials are not likely to cause allergies or irritations.**
- **Universal fit with excellent seal (leakage less than 0,05%).**
- **Low breathing resistance (<1,2 mbar during inhalation, <2,0 mbar during exhalation, at a rate of 160 l/min).**
- **Reduced dead space, well below the maximum allowed.**
- **Good flame resistance and self extinguishing qualities.**
- **Quick and easy donning and doffing.**
- **Can be suspended from the neck, ready for use, with unfastened harness.**
- **Longlasting, high resistance to ozone attacks; suitable for exposure to both low and high temperatures and unaffected by humidity.**
- **Easy to maintain, clean and disinfect.**
- **Compatible with glasses and goggles.**
- **Weight: POLIMASK 230 approx. 160 g.**

## MAIN COMPONENTS

- Synthetic rubber facepiece with wide internal seal for a tight fit.
- Silicon rubber version is also available for better comfort and easy sanitizing.
- Bracket fastener with adjustable buckles for harness.
- Adjustable harness composed of two straps, the upper being divided at the back of head.
- Special threaded inhalation connector.
- Exhalation valve assembly with compensating prechamber.
- Possibility of mounting a prefilter.

## CODE

| | | |
|---|---|---|
| POLIMASK 230/EF+VS A1 P1 | | Cod. **43360020** |



Dispositivi Protezione Individuale D.P.I. S.r.l. - Via di Cervara, 42 00155 Roma – Tel. +39 06 2270051 – Fax +39 06 2290351 - www.dpisekur.com – dpi@dpisekur.com